

## Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### FIG 115.1GG/115.2GG

Resilient Seated Gate Valves. 2 through 12 in. NPS. Valves have a rated working pressure of 232 psi (1600 kPa). Available with the following end connections.

Model	Size, in. (mm)	End Connection
FIG 115.1GG/115.2GG	2, 2 1/2, 3, 4, 6, 8, 10, 12 (50, 65, 80, 100, 150, 200, 250, 300)	Groove x Groove (ISO 6182)

<b>Company Name:</b>	Rapidrop Global Limited
<b>Company Address:</b>	Rutland Business Park, Newark Rd, Peterborough PE15WA, United Kingdom
<b>Company Website:</b>	<a href="http://www.rapidrop.com">http://www.rapidrop.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved