



Valves | Indicating Valves (Butterfly or Valve Type) | **Indicating Valves, Butterfly or Ball Type**

Fig 212, Fig 213, and Fig 214

Product Specification

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		mm	(in)	psi	(kPa)	
Fig. 213	Butterfly Valve, Wafer Body	50, 65, 80, 100, 125, 150, 200, 250, 300	(2, 2 1/2, 3, 4, 5, 6, 8, 10, 12)	300	(2065)	a, b, c
Fig. 214	Butterfly Valve, Lug Body	50, 65, 80, 100, 125, 150, 200, 250, 300	(2, 2 1/2, 3, 4, 5, 6, 8, 10, 12)	300	(2065)	a, b, c
Fig. 212	Butterfly Valve, Grooved Ends	50, 65, 80, 100, 125, 150, 200, 250, 300	(2, 2 1/2, 3, 4, 5, 6, 8, 10, 12)	300	(2065)	a, b, c

Remarks:

- a. Available with dual supervisory switches.
- b. FM Approved for indoor and outdoor service.
- c. FM Approved for aboveground installations only.

Details

Class of Work : 1112 - Indicating Valves

Approval Standard : FM 1112 - Indicating Valves (Butterfly or Ball Type)

Certification Type : FM Approved

Listing Country : United Kingdom

Category : Indicating Valves, Butterfly or Ball Type

Company

Rapidrop Global Limited

Rutland Business Park, Newark Rd, Peterborough
PE1 5WA, United Kingdom
United Kingdom

<http://www.rapidrop.com>